

إعلان طرح عطاء

1. تعلن القيادة العامة للقوات المسلحة الأردنية/ قيادة سلاح الجو الملكي عن طرح العطاء رقم س ج/ت ف/15/2025 وهو عباره عن شراء أنظمة كاميرات مراقبة.
2. على الراغبين بالاشتراك مراجعة قسم المشتريات بقيادة سلاح الجو الملكي خلال ساعات الدوام الرسمي ليومي الثلاثاء والخميس من كل إسبوع ابتداءً من يوم الثلاثاء الموافق 2025/4/15 ولغاية يوم الثلاثاء الموافق 2025/5/6 لإستلام نسخة كشف المواد مقابل (50) خمسون دينار فقط غير مستردة مصطحبين معهم رخصة مهن سارية المفعول وسجل تجاري وشهادة تثبت التسجيل بنظام الفوترة الوطني الإلكتروني ولن ينظر بأي عرض سعر لم يقدمها.
3. اخر موعد لبيع المناقصات يوم الثلاثاء الموافق 2025/5/6 وخلال ساعات الدوام الرسمي.
4. تعاد المناقصات بالظرف المختوم خلال ساعات الدوام الرسمي ليس بعد يوم الخميس الموافق 2025/5/8 ولن تقبل أية مناقصة ترد بعد هذا الوقت.
5. للإطلاع على كشف المواد المطلوبة للعطاء يرجى زيارة الموقع الإلكتروني الرسمي لقيادة سلاح الجو الملكي (WWW.RJAF.MIL.JO).

كشف المواد المطلوبة

#	Item	Description	Qty
1	IP Camera outdoor	Image sensor:1/2.7 "-1/3" CMOS, 4MP Fixed length: (3.6/4/6) mm, Day/Night: ICR , H264,H264+,H265,H265+ FOV-H: 77°, WDR: 120db, Max.IR Distance: (40-50) meter, Min- illumination: (0.01-0.005) lux@f(1.6) 0 lux IR on, working temperature: -30° to +60° ONVIF supported, multi-streaming, frame rate: (20-30) fps, ingress protection: IP67, power POE supported, supported motion detection.	9
2	IP Camera outdoor	Image sensor:1/2.7 "-1/3" CMOS, 4MP Fixed length: (3.6/4/6) mm, Day/Night: ICR , H264,H264+,H265,H265+ FOV-H: 77°, WDR: 120db, Max.IR Distance: (50-60) meter, Min- illumination: (0.01-0.005) lux@f(1.6) 0 lux IR on, working temperature: -30° to +60° ONVIF supported, multi-streaming, frame rate: (20-30) fps, ingress protection: IP67, power POE supported, supported motion detection.	4
3	IP Camera outdoor	Image sensor:1/1.8 "-1/3" CMOS, 4MP Variable focal length: (2.8-12) mm, Day/Night: ICR , H264,H264+,H265,H265+ FOV-H: 77°, WDR: 120db, Max.IR Distance: (20-30) meter, Min- illumination: (0.01-0.005) lux@f(1.6) 0 lux IR on, working temperature: -30° to +60° ONVIF supported, multi-streaming, frame rate: (20-30) fps, ingress protection: IP67, power POE supported, supported motion detection.	36
4	IP Camera indoor	Image sensor:1/2.7 "-1/3" CMOS, 4MP Fixed length: (3.6/4/6) mm, Day/Night: ICR , H264,H264+,H265,H265+ FOV-H: 77°, WDR: 120db, Max.IR Distance: (20-30) meter, Min- illumination: (0.01-0.005) lux@f(1.6) 0 lux IR on, working temperature: -30° to +60° ONVIF supported, multi-streaming, frame rate: (20-30) fps, ingress protection: IP67, power POE supported, supported motion detection.	17
5	IP Camera indoor	Image sensor:1/1.8 "-1/3" CMOS, 4MP Variable focal length: (2.8-12) mm, Day/Night: ICR , H264,H264+,H265,H265+ FOV-H: 77°, WDR: 120db, Max.IR Distance: (20-30) meter, Min- illumination: (0.01-0.005) lux@f(1.6) 0 lux IR on, working temperature: -30° to +60° ONVIF supported, multi-streaming, frame rate: (20-30) fps, ingress protection: IP67, power POE supported, supported motion detection.	16

6	PTZ Camera	Image sensor:1/1.8 "-1/3" CMOS,5MP Minimum zooming: 30X, Day/Night: ICR , H264,H264+,H265,H265+ FOV-H: 77°, WDR≥120db Pan:360°, Tilt: -15° to 90° Max.IR Distance: up to (300) meter, Min- illumination: (0.01-0.005) lux@f(1.6) 0 lux IR on, working temperature: -30° to +60° ONVIF supported, multi-streaming, frame rate: (20-30) fps, ingress protection: IP67, power POE supported, supported motion detection.	3
7	NVR	16 channel, 2 USB, NTSC/PAL, Display: HDMI, VGA, video compression: H264,H264+,H265,H265+ ,Bandwidth: (128- 256)Mbps, support max HDD:2x 6 TB, perimeter protection by camera supported, recording resolution: 4/5 MP	4
8	NVR	8 channel, 2 USB, NTSC/PAL, Display: HDMI, VGA, video compression: H264,H264+,H265,H265+ ,Bandwidth: (80-128) Mbps, support max HDD:4 TB, perimeter protection by camera supported, recording resolution: 4/5 MP	1
9	NVR	4 channel, 2 USB, NTSC/PAL, Display: HDMI, VGA, video compression: H264,H264+,H265,H265+ ,Bandwidth: (80-128) Mbps, support max HDD:4 TB, perimeter protection by camera supported, recording resolution: 4/5 MP	1
10	NVR	4 channel, 2 USB, NTSC/PAL, Display: HDMI, VGA, video compression: H264,H264+,H265,H265+ ,Bandwidth: (80-128) Mbps, support max HDD:2x6TB, perimeter protection by camera supported, recording resolution: 4/5 MP	3
11	NVR	4 channel, 2 USB, NTSC/PAL, Display: HDMI, VGA, video compression: H264,H264+,H265,H265+ ,Bandwidth: (80-128) Mbps, support max HDD:2x1 TB, perimeter protection by camera supported, recording resolution: 4/5 MP	2
12	DVR	16 channel analogue video/support max=8MP/AHD support/BNC interface/ HDD up to 6TB/ USB/HDMI/VGA	1
13	Switch	8 ports POE/2FE/2Gbps/Min 60W/ 250 meter	21
14	Switch	4 ports POE/2FE/2Gbps/Min 60W/ 250 meter	7
15	Switch	16 ports POE/2FE/2Gbps/Min 60W/ 250 meter	1
16	Fiber Termination box	2 input, 4 output ports	16
17	HDD	6 TB	8
18	HDD	1 TB	5
19	Media Converter	2port Ethernet to fiber SC 10/100/1000 with digital (Tx/Rx)	16 pairs
20	Media Converter	Fiber single mode FC to BNC coaxial TX/RX 20KM	10 pairs
21	Media Converter	HDMI to fiber SC 10/100/1000 with digital (Tx/Rx)	5 pairs
22	Patch cords	FC-SC	40
23	Poles	3 meter height, 4 inch diameter, with 2 mounted plate for each one	3
24	LED Screen	55 inch/3HDMI, VGA input	5
25	LED Screen	43 inch/3HDMI, VGA input	5
26	HDMI CABLE	1M	10
27	HDMI CABLE	3M	5
28	HDMI CABLE	5M	2

29	HDMI CABLE	10M	4
30	HDMI CABLE	15M	5
31	HDMI CABLE	20M	2
32	HDMI splitter	4 outputs	4
33	HDMI extender	Up to 120 meter	1
34	وصلة كهرباء	12A	16
35	RJ45	STP+UTP CAT6/A PLUG 100/PACK	12 PACK
36	cabinet	9 U	5
37	cabinet	6 U	8
38	Cable CAT6	ROLL/23 AWG SOLID BARE COPPER, (F/UTP)4PAIR 500 METER	17 Roll
39	Coaxial cable with power	RG59, 75ohm, 200 meter roll	3
40	Power Adapter	12V, 2A	10
41	مواسير بلاستيك	3m/25m	300
42	مفة بلاستيك	25mm	160
43	كوع بلاستيك	25mm	140
44	مرابط بلاستيك	25mm	500
45	علب خارجية ضد الماء	7cm*10cm*10cm	85
46	علب خارجية ضد الماء	50cm*60cm*25cm	30
47	براغي + اسافين	50/1 pack, 6mm	31 pack
48	Poles	4 meter height, 4 inch diameter, with 2 mounted plate for each one	3
49	مواسير بلاستيك	4 inch	250
50	مواسير بلاستيك	1.25 inch	250